

Tegula

Traditional styling.

Tegula is a popular and versatile product that provides an aged appearance, reminiscent of stone setts and ideal for traditional settings. Tegula is created using an innovative aging process and comes in a wide selection of multi-tone colours.

- Processed to give an aged, antique appearance
- Vibrant long-lasting colours
- Significantly reduced efflorescence
- Suitable for both modern or period properties

Ef-Stop®

 A Aged Finish	 Permeable Also available as	 Pedestrian Use Refer to relevant guidance in BS 7533	 Light Traffic	 Commercial Traffic	 Machine Lay	 BIM Level 2
---	---	---	---	--	---	---



SCAN HERE



140 x 140mm



175 x 140mm



173 x 173mm



208 x 173mm



104 x 173mm



240 x 160mm


Single Sizes



130 x 173mm



173 x 173mm



197 x 173mm

Trio 50mm Sizes

All three sizes in one pack



50mm

60mm

80mm

Depths

Tegula



Specification



Product type	Concrete Paving Block
Manufactured to	BS EN 1338:2003
Surface Finish	Processed to give an aged appearance
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Typical tensile splitting strength of >3.6MPa
Slip/Skid risk	Extremely Low
Installed to	BS 7533-3:2005
BS	Plus Q24 110 Create 45-20-64/400
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance	Class 3
Durability (Freeze-thaw)	Class 3
External Fire Performance	Deemed to satisfy. See Commission Decision 2000/553/EC
Reaction to fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 10% (all colours except Natural, Golden & Slate)
Carbon Footprint	50mm 18kgCo ² e/m ² 60mm 24kgCo ² e/m ² 80mm 32kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breem rating www.breem.co.uk	50/60mm: A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved when used in conjunction with a prepared recycled sub-base. 80mm: B , according to the Green Guide to Specification, 4 th Edition 2009. A , can be achieved when used in conjunction with a prepared recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Contact Us

GB: 0844 800 5736
 NI: 028 7964 2411
 ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk

Tegula

Heather

Bracken

Brindle

Slate

Cedar

Charcoal

Golden


Stock

Stock

product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Tegula 50mm	175 x 140 x 50	Bracken, Charcoal, Heather, Slate	YES	13.37	1.91	40.82	546	1503	1493
	140 x 140 x 50	Bracken, Charcoal, Heather, Slate	YES	13.77	1.53	51	702	1550	1531
Tegula Trio 50mm (all three sizes in one pack)	197 x 173 x 50	Bracken, Brindle, Cedar, Charcoal, Golden, Heather, Slate	YES	13.65	1.05	33.3	182	1530	1520
	173 x 173 x 50						182		
	130 x 173 x 50						91		
Tegula 60mm	208 x 173 x 60	Bracken, Cedar, Charcoal, Heather, Slate	YES	12.95	2.16	27.79	360	1810	1800
	173 x 173 x 60	Bracken, Cedar, Charcoal, Heather, Slate	YES	12.56	1.79	33.41	420	1743	1733
Tegula 80mm	240 x 160 x 80	Bracken, Charcoal, Heather, Slate	YES	9.6	1.92	26.03	250	1748	1738
	208 x 173 x 80	Bracken, Charcoal, Heather, Slate	YES	9.72	1.62	27.79	270	1770	1760
	173 x 173 x 80	Bracken, Charcoal, Heather, Slate	YES	9.43	1.35	33.41	315	1717	1707
	104 x 173 x 80	Bracken, Charcoal, Heather, Slate	YES	9.07	1.3	55.58	504	1628	1618

BIM - This product is available to download from our website in BIM Level 2 format. **ML** - This product can be hand or machine laid.

Contact Us

GB: 0844 800 5736
 NI: 028 7964 2411
 ROI: 048 7964 2411

Email

technical@tobermore.co.uk
 sales@tobermore.co.uk

tobermore.co.uk